



## Cylindrical Roller Bearings-VIETNAM C...



6928LLU Bearing 2D drawings and 3D CAD models

140,000 mm x 190,000 mm x 24,000 mm NTN  
6928LLU deep groove ball bearings

Bearing No. 6928LLU

Size	140x190x24 mm
Bore Diameter	140,000 mm
Outer Diameter	190,000 mm
Width	24,000 mm
d	140,000 mm
D	190,000 mm
B	24,000 mm
C	24,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.65
EAN	4547359588163
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric



## Cylindrical Roller Bearings-VIETNAM C...

Long Description	140MM Bore; 190MM Outside Diameter; 24MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	6928LLU/2AS
Weight / LBS	3.624
Bore	5.512 Inch   140 Millimeter
Outer Race Width	0.945 Inch   24 Millimeter
Outside Diameter	7.48 Inch   190 Millimeter
bore diameter:	140 mm
precision rating:	ISO Class 0
outside diameter:	190 mm
finish/coating:	Uncoated
overall width:	24 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	24 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	24 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	1800 rpm
internal clearance:	CN



## Cylindrical Roller Bearings-VIETNAM C...

fillet radius:	1.5 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	3200 RPM
dynamic load capacity:	66500 N
series:	69
static load capacity:	71500 N
manufacturer product page:	<a href="#">Click here</a>