




Cylindrical Roller Bearings-VIETNAM C...



VA201



2Z/VA201



2Z/VA208



2Z/VA228

High Temp Ball Bearing with Grease 6203-2z/Va201 for SKF High Temperature Bearing

Bearing No. 6203-2z/Va201

6203-2z/Va201 Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------|--------------------------|
| Size | 17x40x12 mm |
| Bore Diameter | 17 mm |
| Outer Diameter | 40 mm |
| Width | 12 mm |
| d | 17 mm |
| D | 40 mm |
| B | 12 mm |
| C | 12 mm |
| d1 | 24,5 mm |
| r1 min. | 0,6 mm |
| r2 min. | 0,6 mm |
| D2 | 35 mm |
| Weight | 0,065 Kg |
| Temperature - | 30 to +250 ° |
| Basic static load rating (C0) | 4,75 kN |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.066 |
| EAN | 7316571552019 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |



Cylindrical Roller Bearings-VIETNAM C...

| | |
|---------------------------|--|
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | Polyalkylene Glycol/Graphite Mixture Filled |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 17MM Bore; 40MM Outside Diameter; 12MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Fea |
| Other Features | Deep Groove Extreme Temperature Variant |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Weight / LBS | 0.146 |
| Outside Diameter | 1.575 Inch 40 Millimeter |
| Bore | 0.669 Inch 17 Millimeter |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| d ₁ | 24.5 mm |
| D ₂ | 34.98 mm |
| r _{1,2} min. | 0.6 mm |
| d _a min. | 21.2 mm |
| d _a max. | 24.4 mm |
| D _a max. | 35.8 mm |
| | |



Cylindrical Roller Bearings-VIETNAM C...

| | |
|--------------------------------|-----------|
| r_a max. | 0.6 mm |
| Basic dynamic load rating C | 9.95 kN |
| Basic static load rating C_0 | 4.75 kN |
| Limiting speed | 150 r/min |
| Limiting temperature T max. | 250 ° C |
| Mass bearing | 0.068 kg |